NSN 5945-00-069-1275

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-069-1275

Overall Le	ength:
------------	--------

1.160 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.125 inches single mounting facility

Overall Height:

0.400 inches

Overall Width:

0.875 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Winding Quantity:

2

Coil Quantity:

2

Winding Dc Resistance Rating:

700.0 ohms second winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Features Provided:

Polarized

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

39.0 milliamperes dc all windings

Time Delay:

0.0050 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

Terminal Type And Quantity:

10 pin all functions

NSN 5945-00-069-1275

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300