# NSN 5945-00-069-1998

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-069-1998

### **Overall Length:**

3.750 inches

## Center To Center Distance Between Mounting Facilities Parallel To Length:

3.250 inches first mounting facility

## Center To Center Distance Between Mounting Facilities Parallel To Width:

2.000 inches second mounting facility

#### **Overall Height:**

3.437 inches

**Overall Width:** 

3.750 inches

#### Mounting Slot Width:

0.203 inches first mounting facility

#### **Case Material:**

Plastic

#### **Environmental Protection:**

Dustproof

#### **Unthreaded Mounting Hole Diameter:**

0.173 inches second mounting facility

# Winding Quantity:

1

## Coil Quantity:

1

# Winding Dc Resistance Rating:

175.0 ohms single winding

#### **Duty Type:**

Continuous

#### Mounting Facility Type And Quantity:

2 unthreaded hole second mounting facility

#### Mounting Facility Pattern:

In-line second mounting facility

#### Nonpile-up Main Contact Arrangement:

3 pole, single throw, normally open, momentary action

#### Nonpile-up Auxiliary Contact Arrangement:

3 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action

#### Auxiliary Contact Maximum Voltage Rating In Volts:

220.0 ac

## Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

# Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 amperes ac resistive load

# Main Contact Maximum Voltage Rating In Volts:

600.0 ac

# NSN 5945-00-069-1998

Electromagnetic Relay - Page 2 of 2



## Auxiliary Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

# Terminal Type And Quantity:

16 screw all functions

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A03300