## NSN 5945-00-069-6740

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-069-6740
Overall Length:
5.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.620 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.755 inches single mounting facility
Overall Height:
9.375 inches
Overall Width:
4.120 inches
Environmental Protection:
Salt spray resistant
Unthreaded Mounting Hole Diameter:
0.199 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Winding Dc Resistance Rating:
75.0 ohms first winding
Duty Type:
Continuous
Arc Quenching Method:
Capacitor
Mounting Facility Type And Quantity:
4 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Latching contacts
Cubic Measure:
202.781 cubic inches
Mounting Facility Pattern:
Rectangular single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp:

20000.0 volts ac 25 degrees celsius second winding

## NSN 5945-00-069-6740

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

250.0 ac and 125.0 dc

**Terminal Type And Quantity:** 

10 screw all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A03300