

View Online at <https://aerobasegroup.com/nsn/5945-00-070-7118>

Thread Class:

2a single mounting facility

Thread Length:

0.344 inches single mounting facility and 0.375 inches single mounting facility

Overall Length:

1.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.690 inches single mounting facility and 0.710 inches single mounting facility

Overall Height:

1.041 inches

Overall Width:

0.810 inches

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

9.0 kilohms single winding and 13.5 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

0.851 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Triangle single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Current Rating And Type:

6.5 milliamperes dc single winding

Time Delay:

0.006 seconds fixed operate time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.290 inches single mounting facility and 0.310 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

73.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

14 wire hook all functions

Specification Data:

00724-47-00123-001 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300