

View Online at <https://aerobasegroup.com/nsn/5945-00-070-7118>

**Thread Class:**

2a single mounting facility

**Thread Length:**

0.344 inches single mounting facility and 0.375 inches single mounting facility

**Overall Length:**

1.010 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.690 inches single mounting facility and 0.710 inches single mounting facility

**Overall Height:**

1.041 inches

**Overall Width:**

0.810 inches

**Environmental Protection:**

Dustproof

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

9.0 kilohms single winding and 13.5 kilohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

3 threaded stud single mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

0.851 cubic inches

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Triangle single mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Current Rating And Type:**

6.5 milliamperes dc single winding

**Time Delay:**

0.006 seconds fixed operate time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

0.290 inches single mounting facility and 0.310 inches single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

73.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

14 wire hook all functions

**Specification Data:**

00724-47-00123-001 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300