NSN 5945-00-075-8529

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-075-8529

Overall Length:
1.010 inches
Overall Height:
1.000 inches
Overall Width:
0.610 inches
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
688.5 ohms single winding and 841.5 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Arc Quenching Method: Air
Air
Air Mounting Facility Type And Quantity:
Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type:
Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility
Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure:
Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches
Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement:
Air Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type:
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay:
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay: 0.006 seconds fixed operate time
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp:
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 1.0 amperes ac resistive load and 2.0 amperes dc resistive load
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 0.616 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, double throw, one position momentary Operating Current Rating And Type: 22.0 milliamperes dc single winding Time Delay: 0.006 seconds fixed operate time Operating Voltage Rating And Type At Specificationified Temp: 13.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:

14 pin all functions

NSN 5945-00-075-8529

Electromagnetic Relay - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300