# NSN 5945-00-076-0233

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-076-0233

#### **Overall Length:**

1.322 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.065 inches single mounting facility and 1.075 inches single mounting facility

#### **Overall Height:**

0.910 inches

#### **Overall Width:**

0.400 inches

#### Mounting Slot Width:

0.115 inches single mounting facility and 0.125 inches single mounting facility

#### **Case Material:**

Metal

**Environmental Protection:** 

Dustproof

#### Fragility Factor:

#### Moderately rugged

Winding Quantity:

#### 2

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

2

Winding Dc Resistance Rating:

630.0 ohms single winding

#### Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 slotted hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Latching contacts

**Cubic Measure:** 

0.481 cubic inches

#### **Mounting Facility Pattern:**

In-line single mounting facility

#### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.005 seconds fixed operate and release time

## NSN 5945-00-076-0233

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius all windings

### Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Terminal Type And Quantity:

10 pin all functions

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03300