

View Online at <https://aerobasegroup.com/nsn/5945-00-079-9429>

Overall Length:

1.160 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.125 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility

Overall Height:

Between 0.875 inches and 1.110 inches

Overall Width:

0.400 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.096 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

992.0 ohms single winding and 1.215 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Current Rating And Type:

7.0 milliamperes dc single winding

Time Delay:

0.006 seconds fixed operate and release time

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Terminal Type And Quantity:

8 pin all functions

Fsc Application Data (non-core):

Relay armature, except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300