# NSN 5945-00-081-5116

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-081-5116

# Thread Class:

2b second mounting facility

# **Thread Direction:**

Right-hand second mounting facility

# Overall Length:

3.380 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

1.750 inches second mounting facility

# **Overall Height:**

7.480 inches

**Overall Width:** 

3.090 inches

# Case Material:

Plastic

# **Environmental Protection:**

Dustproof

# Unthreaded Mounting Hole Diameter:

0.199 inches first mounting facility

# Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches second mounting facility

# Fragility Factor:

Moderately rugged

# Frequency In Hertz:

60.0

# Winding Quantity:

1

## Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Duty Type:

Continuous

## Arc Quenching Method:

Air

# Mounting Facility Type And Quantity:

4 unthreaded hole first mounting facility

## Storage Type:

General purpose warehouse

## **Cubic Measure:**

78.123 cubic inches

## Thready Qty Per Inch (tpi):

32 second mounting facility

# NSN 5945-00-081-5116

Electromagnetic Relay - Page 2 of 2



**Thread Size:** 0.164 inches second mounting facility **Mounting Facility Pattern:** Rectangular second mounting facility Nonpile-up Main Contact Arrangement: 2 pole, double throw, one position momentary **Time Delay:** 1.50 seconds adjustable operate time and 15.00 seconds adjustable operate time **Operating Voltage Rating And Type At Specificationified Temp:** 480.0 volts ac 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load and 15.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 240.0 ac and 30.0 dc **Energizing Element Power Rating:** 8.0 watts **Thread Series Designator:** Unc second mounting facility **Terminal Type And Quantity:** 8 screw all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300