

View Online at <https://aerobasegroup.com/nsn/5945-00-081-6670>

Overall Length:

2.687 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

Overall Height:

2.656 inches

Overall Width:

2.218 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.187 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.750 inches single mounting facility

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

150.0 ohms all windings

Duty Type:

Intermittent

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

3m

Mounting Facility Pattern:

Rectangular single mounting facility

Operating Current Rating And Type:

0.3 amperes dc all windings

Time Delay:

0.02 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

20.0 milliamperes ac resistive load and 20.0 milliamperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

200.0 ac and 28.0 dc

Terminal Type And Quantity:

11 pin contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300