NSN 5945-00-082-0968

Electrical Solenoid - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5945-00-082-0968

Cylindrical frame
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.285 inches
Body Length:
2.750 inches
Case Material:
Steel
Case Surface Treatment:
Nickel
Environmental Protection:
Humidity proof
Unthreaded Mounting Hole Diameter:
0.125 inches
Maximum Operating Temp:
125.0 degrees celsius
Mounting Base Length:
1.250 inches
Mounting Base Width:
1.593 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1 and 1
Electrical Resistance:
8.00 ohms and 96.00 ohms
Duty Type:
Continuous
Terminal Location:
End opposite actuator
Voltage Rating In Volts:
30.0 dc
Mounting Facility Type And Quantity:
4 unthreaded hole
Current Rating:
25.0 milliamperes and 3.0 amperes
Actuator Stroke Type:
Pull and push

1.00 ounces

Linear Force Delivered:

NSN 5945-00-082-0968 Electrical Solenoid - Page 2 of 2



Power Takeoff Connection Type:
Internal plunger
Energizing Stroke Maximum Length:
0.266 inches
Mounting Facility Pattern:
Four position rectangular
Test Data Document:
82577-970001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 solder stud
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A134a0