## NSN 5945-00-084-3390

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-084-3390

| Overall Length:   |
|---|
| 1.330 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.070 inches single mounting facility                                     |
| Overall Height:   |
| 0.508 inches  |
| Overall Width:  |
| 0.156 inches  |
| Mounting Slot Width:  |
| 0.120 inches single mounting facility                                     |
| Environmental Protection:   |
| Hermetic  |
| Winding Quantity:   |
| 2   |
| Coil Quantity:  |
| 2   |
| Winding Dc Resistance Rating:   |
| 325.0 ohms second winding   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 2 slotted hole single mounting facility                                   |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Nonpile-up Main Contact Arrangement:                                      |
| 2 pole, double throw, both positions maintained                           |
| Operating Current Rating And Type:  |
| 17.5 milliamperes dc second winding                                       |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 5.70 volts dc 25 degrees celsius all windings                             |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 2.0 amperes ac resistive load and 2.0 amperes dc resistive load           |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 120.0 ac and 28.0 dc  |
| Terminal Type And Quantity:   |
| 10 wire hook all functions  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5945-00-084-3390

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300