

View Online at <https://aerobasegroup.com/nsn/5945-00-086-0710>

Overall Length:

3.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.750 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

Overall Height:

3.090 inches

Overall Width:

3.650 inches

Environmental Protection:

Watertight

Unthreaded Mounting Hole Diameter:

0.156 inches single mounting facility

End Application:

Asr7

Frequency In Hertz:

60.0

Winding Quantity:

1

Duty Type:

Continuous

Mounting Facility Type And Quantity:

6 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Time Delay:

60.0000 seconds adjustable operate time and 300.0000 seconds adjustable operate time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

10.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

125.0 ac

Special Features:

Lfunction, timer, interval, 115v; reference data, ti-6310.23, fa 8200e, 1k5, pg 10-126, vol 2, sec 10-11/ti-6310.41, fa 8200f, 1k5, pg 10-126, vol 2, sec 10-11/ti-6310.4a, fa 8200, 1k5, pg 10-97, vol 2, sec 10-11

Terminal Type And Quantity:

3 screw contacts

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300