## NSN 5945-00-086-2877



Electrical Solenoid - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-00-086-2877 **Thread Class:** 2b mounting facility hole **Thread Direction:** Right-hand mounting facility hole **Body Style:** U-frame **Center To Center Distance Between Mounting Facilities Parallel To Length:** 0.500 inches **Center To Center Distance Between Mounting Facilities Parallel To Width:** 0.437 inches **Body Length:** 1.125 inches **Body Width:** 0.750 inches **Body Height:** 0.812 inches **Case Material:** Any acceptable **Case Surface Treatment:** Any acceptable **Environmental Protection:** Any acceptable Frequency In Hertz: 60.0 **Inclosure Type:** Fully enclosed **Magnetic Coil Quantity: Electrical Resistance:** 200.00 ohms **Duty Type:** Continuous **Terminal Location:** One side **Voltage Rating In Volts:** 120.0 ac **Mounting Facility Type And Quantity:** 2 threaded hole **Current Rating:** 

0.436 amperesThready Qty Per Inch (tpi):32 mounting facility hole

## **NSN 5945-00-086-2877** Electrical Solenoid - Page 2 of 2



Actuator Stroke Type:
Pull and push
Linear Force Delivered:
0.50 ounces
Power Takeoff Connection Type:
Plain
Energizing Stroke Maximum Length:
0.375 inches
Thread Size:
0.138 inches mounting facility hole
Mounting Facility Pattern:
Two position diagonal
Thread Series Designator:
Unc mounting facility hole
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A134a0