## NSN 5945-00-087-9225

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-087-9225

| Thread Class:   |
|---|
| 2a single mounting facility   |
| Overall Length:   |
| 0.980 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.350 inches single mounting facility                                     |
| Overall Height:   |
| 1.270 inches  |
| Overall Width:  |
| 0.610 inches  |
| Environmental Protection:   |
| Hermetic  |
| Winding Quantity:   |
| 1   |
| Purpose For Which Designed:   |
| General   |
| Coil Quantity:  |
| 1   |
| Winding Dc Resistance Rating:   |
| 500.0 ohms single winding   |
| Duty Type:  |
| Continuous  |
| Mounting Facility Type And Quantity:                                      |
| 3 threaded stud single mounting facility                                  |
| Thready Qty Per Inch (tpi):   |
| 40 single mounting facility   |
| Thread Size:  |
| 0.112 inches single mounting facility                                     |
| Mounting Facility Pattern:  |
| In-line single mounting facility  |
| Nonpile-up Main Contact Arrangement:                                      |
| 4 pole, double throw, one position momentary                              |
| Operating Voltage Rating And Type At Specificationified Temp:             |
| 26.5 volts dc 25 degrees celsius single winding                           |
| Main Contact Load Current Rating At Maximum Rated Voltage:                |
| 1.0 amperes ac resistive load and 2.0 amperes dc resistive load           |
| Main Contact Maximum Voltage Rating In Volts:                             |
| 115.0 ac and 28.0 dc  |
| Thread Series Designator:   |
| Unc single mounting facility  |
| Terminal Type And Quantity:   |

14 pin all functions

## NSN 5945-00-087-9225

Electromagnetic Relay - Page 2 of 2



| - |    |    |    |   |   |
|---|----|----|----|---|---|
| • | he | 1+ | 18 | Δ | • |
|   |    |    |    |   |   |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300