## NSN 5945-00-088-1517

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-088-1517

## **Thread Class:** 2a single mounting facility **Thread Direction:** Right-hand single mounting facility **Overall Length:** 1.531 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.187 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.187 inches single mounting facility **Overall Height:** 2.087 inches **Overall Width:** 1.531 inches **Case Material:** Metal **Environmental Protection:** Hermetic **Fragility Factor:** Moderately rugged Winding Quantity: 1 **Purpose For Which Designed:** General **Coil Quantity:** 1 Winding Dc Resistance Rating: 160.0 ohms single winding **Duty Type:** Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 4 threaded stud single mounting facility Storage Type: General purpose warehouse **Cubic Measure:** 4.891 cubic inches Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:**

0.138 inches single mounting facility

## NSN 5945-00-088-1517

Electromagnetic Relay - Page 2 of 2

**Mounting Facility Pattern:** Rectangular single mounting facility Nonpile-up Main Contact Arrangement: 3 pole, single throw, normally open, momentary action **Operating Voltage Rating And Type At Specificationified Temp:** 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 20.0 amperes ac motor load and 20.0 amperes dc motor load Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 28.0 dc **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 8 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300

