

View Online at <https://aerobasegroup.com/nsn/5945-00-089-2039>

Overall Length:

6.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.406 inches single mounting facility

Overall Height:

6.120 inches

Overall Width:

6.120 inches

Unthreaded Mounting Hole Diameter:

0.281 inches single mounting facility

Frequency In Hertz:

60.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

113.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

5 pole, single throw, normally open, momentary action

Operating Current Rating And Type:

150.0 milliamperes ac single winding

Nonpile-up Auxiliary Contact Arrangement:

2 two circuit, both positions maintained

Auxiliary Contact Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Operating Voltage Rating And Type At Specificationified Temp:

440.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

45.0 amperes ac inductive load

Main Contact Maximum Voltage Rating In Volts:

440.0 ac

Terminal Type And Quantity:

20 pin all functions

Fsc Application Data (non-core):

Except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300