

View Online at <https://aerobasegroup.com/nsn/5945-00-102-6154>

**Thread Class:**

2a single mounting facility

**Overall Length:**

1.080 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.488 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.220 inches single mounting facility

**Overall Height:**

0.810 inches

**Overall Width:**

0.830 inches

**Environmental Protection:**

Hermetic

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

1.2 kilohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

2 threaded stud single mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Thready Qty Per Inch (tpi):**

40 single mounting facility

**Thread Size:**

0.112 inches single mounting facility

**Mounting Facility Pattern:**

Diagonal single mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

300.0 milliamperes ac resistive load and 1.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

8 pin all functions

**Specification Data:**

81349-mil-r-5757/10 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300