# NSN 5945-00-110-3458

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-110-3458

## Thread Class:

2a single mounting facility

## **Thread Direction:**

Right-hand single mounting facility

## **Overall Length:**

1.630 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

0.937 inches single mounting facility

#### **Overall Height:**

2.640 inches

#### **Overall Width:**

1.410 inches

## Case Material:

Metal

#### **Environmental Protection:**

Shock resistant and vibration resistant

#### **Fragility Factor:**

Moderately rugged

#### **Contact Material:**

Silver

## Winding Quantity:

1

## Purpose For Which Designed:

General

## **Coil Quantity:**

1

## Winding Dc Resistance Rating:

245.0 ohms single winding

#### **Duty Type:**

Continuous

#### Mounting Facility Type And Quantity:

3 threaded stud single mounting facility

#### Storage Type:

General purpose warehouse

#### Cubic Measure:

6.067 cubic inches

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.138 inches single mounting facility

#### Mounting Facility Pattern:

Triangle single mounting facility

## NSN 5945-00-110-3458

Electromagnetic Relay - Page 2 of 2



Nonpile-up Main Contact Arrangement: 1 pole, single throw, normally open, momentary action Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: 1.187 inches single mounting facility **Operating Voltage Rating And Type At Specificationified Temp:** 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 60.0 amperes dc resistive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 5 wire hook all functions Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A03300