NSN 5945-00-113-2822

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-113-2822

| Center To Center Distance Between Mounting Facilities Parallel To Length: 2.625 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coll Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A03300 | Overall Length: |
|---|-------------------|
| Center To Center Distance Between Mounting Facilities Parallel To Length: 2.625 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| 2.625 inches single mounting facility Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts do 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | |
| Center To Center Distance Between Mounting Facilities Parallel To Width: 1.250 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | |
| 1.250 inches single mounting facility Overall Height: 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | |
| Overall Height: 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | - |
| 3.000 inches Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig: | |
| Overall Width: 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig: | - |
| 2.000 inches Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Environmental Protection: Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Hermetic Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Unthreaded Mounting Hole Diameter: 0.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| O.187 inches single mounting facility Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Winding Quantity: 1 Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | - |
| Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Coil Quantity: 1 Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Duty Type: Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Continuous Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Mounting Facility Type And Quantity: 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| 4 unthreaded hole single mounting facility Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Features Provided: Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Polarized Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Mounting Facility Pattern: Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Rectangular single mounting facility Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| 28.0 volts dc 25 degrees celsius single winding Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Terminal Type And Quantity: 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| 2 pin energizing element Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: | |
| N/a Unit Of Measure: Demilitarization: No Fiig: | |
| Unit Of Measure: Demilitarization: No Fiig: | |
| Demilitarization: No Fiig: | |
| No Fiig: | Unit Of Measure: |
| No Fiig: | |
| Fiig: | Demilitarization: |
| - | |
| A03300 | Fiig: |
| | A03300 |