NSN 5945-00-113-5345

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-113-5345

view Offilitie at https://defobasegroup.com/nsi//3345-00-113-3345
Overall Length:
1.180 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches single mounting facility
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.125 inches single mounting facility
Overall Height:
0.600 inches
Overall Width:
0.410 inches
Mounting Slot Width:
1.062 inches single mounting facility and 1.078 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Features Provided:
Polarized
Cubic Measure:
0.290 cubic inches
Mounting Facility Pattern:
Diagonal single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary

Time Delay:

0.004 seconds fixed operate and release time

NSN 5945-00-113-5345

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

750.0 milliamperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300