NSN 5945-00-113-5346

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-113-5346

| Overall Length: |
|---|
| 5.190 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.583 inches single mounting facility |
| Overall Height: |
| 2.970 inches |
| Overall Width: |
| 2.560 inches |
| Environmental Protection: |
| Dust tight and shock resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.266 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 56.0 ohms single winding |
| Duty Type: |
| Intermittent |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Features Provided: |
| Polarized |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Operating Current Rating And Type: |
| 625.0 milliamperes dc single winding |
| Auxiliary Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Terminal Type And Quantity: |
| 2 screw energizing element |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5945-00-113-5346

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300