NSN 5945-00-115-7213

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-115-7213
Overall Length:
2.187 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.844 inches single mounting facility
Overall Height:
2.094 inches
Overall Width:
0.700 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.147 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
2
Purpose For Which Designed:
General
Coil Quantity:
2
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized and latching contacts
Cubic Measure:
3.206 cubic inches
Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.5 amperes ac motor load and 1.5 amperes dc motor load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

NSN 5945-00-115-7213

Electromagnetic Relay - Page 2 of 2



Test Data Document:

81349-mil-r-6106 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal	Type	And	Quantity	y:
----------	------	-----	----------	----

10 pin all functions

Specification Data:

96906-ms25455 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300

Mil-std (military Standard):

Mil-r-6106 spec.