NSN 5945-00-118-8222

Electromagnetic Relay - Page 1 of 2

Thread Class:

Thread Direction:

2a single mounting facility

Right-hand single mounting facility



View Online at https://aerobasegroup.com/nsn/5945-00-118-8222

| Overall Length: |
|--|
| 1.165 inches |
| Overall Height: |
| 1.397 inches |
| Overall Width: |
| 0.735 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Silver |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 700.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 1.196 cubic inches |
| Thready Qty Per Inch (tpi): |
| 48 single mounting facility |
| Thread Size: |
| 0.099 inches single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| |
| 4 pole, double throw, one position momentary |

NSN 5945-00-118-8222

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp: 24.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 5.0 amperes ac resistive load and 5.0 amperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 14 tab, solder lug all functions Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A03300