NSN 5945-00-122-8703

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-122-8703

Overall Length:
3.212 inches
Overall Height:
2.875 inches
Overall Width:
3.000 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 1 plug-in terminal single mounting facility
1 plug-in terminal single mounting facility
1 plug-in terminal single mounting facility Storage Type:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes ac resistive load
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Terminal Type And Quantity:
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Terminal Type And Quantity: 10 pin all functions
1 plug-in terminal single mounting facility Storage Type: General purpose warehouse Cubic Measure: 27.703 cubic inches Nonpile-up Main Contact Arrangement: 4 pole, single throw, normally open, momentary action Operating Voltage Rating And Type At Specificationified Temp: 28.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 150.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac Terminal Type And Quantity: 10 pin all functions Shelf Life:

NSN 5945-00-122-8703

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300