

View Online at <https://aerobasegroup.com/nsn/5945-00-127-1362>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.220 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.220 inches single mounting facility

Overall Height:

1.510 inches

Overall Width:

0.435 inches

Environmental Protection:

Hermetic

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.488 inches single mounting facility

Contact Material:

Silver

Contact Surface Treatment:

Gold

Frequency In Hertz:

400.0

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

4.8 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

115.0 volts ac 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver or contact surfaces gold

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300