

View Online at <https://aerobasegroup.com/nsn/5945-00-127-1421>

**Overall Length:**

3.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.375 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.874 inches single mounting facility

**Overall Height:**

1.530 inches

**Overall Width:**

2.750 inches

**Environmental Protection:**

Dustproof

**Unthreaded Mounting Hole Diameter:**

0.166 inches single mounting facility

**End Application:**

Wasp class lhd; iwo jima class lph; nimitz class cvn; mars class t-afs 1; tarawa class lha; whidbey island class lsd; virginia class cgn (41); emory s. Island class as; forrestal class cv

**Frequency In Hertz:**

60.0

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

3.45 kilohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

6 unthreaded hole single mounting facility

**Pile-up Main Contact Form Arrangement:**

23c

**Mounting Facility Pattern:**

Rectangular single mounting facility

**Operating Current Rating And Type:**

20.0 milliamperes ac single winding

**Criticality Code Justification:**

Feat

**Operating Voltage Rating And Type At Specificationified Temp:**

115.0 volts ac 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

5.0 amperes ac resistive load and 5.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 115.0 dc

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

71 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300