NSN 5945-00-129-5710

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-129-5710

Overall Length:
0.800 inches
Overall Height:
0.890 inches
Overall Width:
0.400 inches
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
12.0 kilohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
1 terminal single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.284 cubic inches
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
4.5 milliamperes dc single winding
Time Delay:
0.005 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
115.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes ac resistive load and 3.0 amperes dc resistive load

NSN 5945-00-129-5710

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Terminal Type And Quantity:

8 wire lead all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300