

View Online at <https://aerobasegroup.com/nsn/5945-00-133-0439>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Thread Length:

0.500 inches single mounting facility

Overall Length:

3.000 inches

Overall Diameter:

1.380 inches

Environmental Protection:

Airtight

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

265.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 threaded bushing single mounting facility

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.8125 inches single mounting facility

Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

Time Delay:

0.018 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

12000.0 ac and 12000.0 dc

Test Data Document:

81349-mil-r-83725 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un single mounting facility

Terminal Type And Quantity:

5 pin all functions

Specification Data:

81349-mil-r-83725/1 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300