NSN 5945-00-138-1178

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-138-1178

Thread Class:
2b mounting facility hole
Body Style:
Enclosed frame
Body Diameter:
2.000 inches
Body Length:
2.000 inches
Body Height:
2.000 inches
Case Material:
Metal
Case Surface Treatment:
Any acceptable
Mounting Base Width:
1.000 inches
Frequency In Hertz:
Between 50.0 and 60.0
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1
Duty Type:
Continuous
Continuous Terminal Location:
Terminal Location:
Terminal Location: Circumference
Terminal Location: Circumference Electric Power Rating:
Terminal Location: Circumference Electric Power Rating: 14.0 watts
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts:
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity:
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi):
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole Actuator Stroke Type:
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole Actuator Stroke Type: Push
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole Actuator Stroke Type: Push Linear Force Delivered:
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole Actuator Stroke Type: Push Linear Force Delivered: 1.50 ounces
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole Actuator Stroke Type: Push Linear Force Delivered: 1.50 ounces Power Takeoff Connection Type:
Terminal Location: Circumference Electric Power Rating: 14.0 watts Voltage Rating In Volts: 24.0 ac Mounting Facility Type And Quantity: 1 threaded hole Thready Qty Per Inch (tpi): 10 mounting facility hole Actuator Stroke Type: Push Linear Force Delivered: 1.50 ounces Power Takeoff Connection Type: Internal plunger

NSN 5945-00-138-1178 Electrical Solenoid - Page 2 of 2



Mounting Facility Pattern:
Single position
Thread Series Designator:
Unc mounting facility hole
Terminal Type And Quantity:
2 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A134a0