# NSN 5945-00-139-2409

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-139-2409

## Overall Length:

3.218 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.611 inches single mounting facility

### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.375 inches single mounting facility

#### **Overall Height:**

2.310 inches

**Overall Width:** 

1.827 inches

#### **Unthreaded Mounting Hole Diameter:**

0.156 inches single mounting facility

**Fragility Factor:** 

#### Moderately rugged

Contact Material:

#### Silver

Winding Quantity:

```
2
```

**Purpose For Which Designed:** 

General

**Coil Quantity:** 

2

Winding Dc Resistance Rating:

52.0 ohms all windings

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

#### Storage Type:

General purpose warehouse

#### **Features Provided:**

Latching contacts

Cubic Measure:

13.581 cubic inches

**Mounting Facility Pattern:** 

Rectangular single mounting facility

#### Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

### **Operating Current Rating And Type:**

235.0 milliamperes dc all windings

## NSN 5945-00-139-2409

Electromagnetic Relay - Page 2 of 2



**Time Delay:** 0.025 seconds fixed operate time **Operating Voltage Rating And Type At Specificationified Temp:** 12.0 volts dc 25 degrees celsius all windings Main Contact Load Current Rating At Maximum Rated Voltage: 10.0 amperes ac resistive load Main Contact Maximum Voltage Rating In Volts: 115.0 ac **Energizing Element Power Rating:** 4.0 watts **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Terminal Type And Quantity:** 22 tab, solder lug all functions Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A03300