NSN 5945-00-140-4094

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-140-4094

view Offline at https://aerobasegroup.com/hsh/5545-00-140-4054
Overall Length:
1.330 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.062 inches single mounting facility
Overall Height:
0.400 inches
Overall Width:
0.875 inches
Environmental Protection:
Hermetic
Unthreaded Mounting Hole Diameter:
0.160 inches single mounting facility and 0.166 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
700.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.465 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Out and the se Outman to Detting a And Towns

Operating Current Rating And Type:

50.0 milliamperes dc single winding

Time Delay:

0.0060 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

NSN 5945-00-140-4094

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Energizing Element Power Rating:

330.0 milliwatts

Terminal Type And Quantity:

8 wire hook all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300