## NSN 5945-00-142-8910

Electromagnetic Relay - Page 1 of 2

Contact terminals 3, 4, 5 and 6 carry 5 amps



View Online at https://aerobasegroup.com/nsn/5945-00-142-8910

Thread Class:
2a single mounting facility
Overall Length:
2.505 inches
Overall Height:
1.440 inches
Overall Width:
1.648 inches
Environmental Protection:
Hermetic
Winding Quantity:
1
Coil Quantity:
1
Winding Dc Resistance Rating:
300.0 ohms single winding
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Features Provided:
Polarized
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally open, momentary action and 4 pole, double throw, one position momentary
Time Delay:
0.022 seconds fixed operate time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.187 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
26.5 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
2.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
50.0 dc
Special Features:

## NSN 5945-00-142-8910

Electromagnetic Relay - Page 2 of 2



Thread Series Designator:
---------------------------

Unc single mounting facility

**Terminal Type And Quantity:** 

16 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300