NSN 5945-00-148-5704

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-148-5704

Thread Class:
3a mounting facility bushing
Body Style:
Cylindrical frame
Body Diameter:
1.500 inches
Body Length:
3.360 inches
Environmental Protection:
Vibration resistant
Maximum Operating Temp:
235.0 degrees fahrenheit
Actuator Length:
0.710 inches
Fragility Factor:
Moderately rugged
Actuator Diameter:
0.622 inches
Inclosure Type:
Fully enclosed
Magnetic Coil Quantity:
1
•
Electrical Resistance:
Electrical Resistance:
Electrical Resistance: 9.00 ohms
Electrical Resistance: 9.00 ohms Duty Type:
Electrical Resistance: 9.00 ohms Duty Type: Intermittent
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location:
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts:
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity:
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type:
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi):
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 14 mounting facility bushing
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 14 mounting facility bushing Actuator Stroke Type:
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 14 mounting facility bushing Actuator Stroke Type: Pull
Electrical Resistance: 9.00 ohms Duty Type: Intermittent Terminal Location: Circumference Voltage Rating In Volts: 24.0 dc Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 14 mounting facility bushing Actuator Stroke Type: Pull Linear Force Delivered:

Plain

NSN 5945-00-148-5704 Electrical Solenoid - Page 2 of 2



Energizing Stroke Maximum Length:
0.250 inches
Thread Size:
1.000 inches mounting facility bushing
Mounting Facility Pattern:
Single position
Thread Series Designator:
Unf mounting facility bushing
Terminal Type And Quantity:
6 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A134a0