## NSN 5945-00-152-8230

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-152-8230

**Thread Class:** 

2a single mounting facility

**Thread Direction:** 

Right-hand single mounting facility

Thread Length:

0.480 inches single mounting facility

**Overall Length:** 

1.300 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.940 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches single mounting facility

**Overall Height:** 

2.543 inches

**Overall Width:** 

1.060 inches

**Environmental Protection:** 

Fungus proof

**Winding Quantity:** 

\_

**Coil Quantity:** 

2

Winding Dc Resistance Rating:

1.05 kilohms all windings

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

2 threaded stud single mounting facility

**Features Provided:** 

Latching contacts

Thready Qty Per Inch (tpi):

40 single mounting facility

**Thread Size:** 

0.112 inches single mounting facility

**Mounting Facility Pattern:** 

Diagonal single mounting facility

**Nonpile-up Main Contact Arrangement:** 

1 pole, single throw, normally closed, momentary action

**Operating Current Rating And Type:** 

100.0 microamperes dc all windings

Operating Voltage Rating And Type At Specificationified Temp:

200.0 volts dc 25 degrees celsius all windings

## NSN 5945-00-152-8230

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

25.0 milliamperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

200.0 dc

**Special Features:** 

Three terminals common to coil and contacts

**Thread Series Designator:** 

Unc single mounting facility

**Terminal Type And Quantity:** 

9 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A03300