NSN 5945-00-162-1532

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-162-1532

Thread Class:	
2a single mounting facility	
Thread Direction:	
Right-hand single mounting facility	
Thread Length:	
0.177 inches single mounting facility	
Overall Length:	
0.940 inches	
Overall Height:	
1.384 inches	
Overall Width:	
0.735 inches	
Case Material:	
Plastic	
Environmental Protection:	
Dustproof	
Fragility Factor:	
Moderately rugged	
Contact Material:	
Silver	
Contact Surface Treatment:	
Gold	
Winding Quantity:	
1	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
5.8 kilohms single winding	
Duty Type:	
Continuous	
Mounting Facility Type And Quantity:	
1 threaded stud single mounting facility	
Storage Type:	
General purpose warehouse	
Thready Qty Per Inch (tpi):	
48 single mounting facility	
Thread Size:	
0.099 inches single mounting facility	
Nonpile-up Main Contact Arrangement:	
2 pole, double throw, one position momentary	
Operating Voltage Rating And Type At Specificationified Tem	р
72.0 volts dc 25 degrees celsius single winding	

NSN 5945-00-162-1532

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 26.0 dc

Energizing Element Power Rating:

2.6 watts

Precious Material And Location:

Contacts silver and contact surfaces gold

Precious Material:

Silver and gold

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300