NSN 5945-00-166-9375

Electromagnetic Relay - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5945-00-166-9375

| Overall Length: |
|---|
| 5.406 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.375 inches single mounting facility |
| Overall Height: |
| 2.687 inches |
| Overall Width: |
| 3.375 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.187 inches single mounting facility |
| Frequency In Hertz: |
| 60.0 |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action |
| Time Delay: |
| 0.20 seconds adjustable operate time and 1.00 minutes adjustable operate time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 480.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.2 amperes ac resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 600.0 ac |
| Terminal Type And Quantity: |
| 6 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5945-00-166-9375

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300