NSN 5945-00-170-5885

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-170-5885

Inread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
1.910 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.940 inches single mounting facility
Overall Height:
2.940 inches
Overall Width:
1.310 inches
Environmental Protection:
Hermetic
Contact Material:
Silver
Contact Surface Treatment:
Cadmium plated
Frequency In Hertz:
400.0
Winding Quantity:
1
Coil Quantity:
1
Duty Type:
Continuous
Mounting Facility Type And Quantity:
3 threaded stud single mounting facility
Thready Qty Per Inch (tpi):
32 single mounting facility
Thread Size:
0.138 inches single mounting facility
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
3.2 amperes ac single winding
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle
1.190 inches single mounting facility
Main Contact Load Current Rating At Maximum Rated Voltage:
5.0 amperes ac resistive load and 500.0 milliamperes dc resistive load

NSN 5945-00-170-5885

Electromagnetic Relay - Page 2 of 2



Main Contact Maximum Voltage Rating In Volts: 115.0 ac and 120.0 dc Precious Material And Location: Contacts silver Precious Material: Silver Thread Series Designator: Unc single mounting facility Terminal Type And Quantity: 8 wire hook all functions Shelf Life: N/a Unit Of Measure: - Demilitarization:

No Fiig: A03300