

View Online at <https://aerobasegroup.com/nsn/5945-00-172-7707>

Overall Length:

1.025 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.615 inches second mounting facility and 0.635 inches second mounting facility

Overall Height:

1.010 inches

Overall Width:

1.025 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.155 inches second mounting facility and 0.161 inches second mounting facility

Fragility Factor:

Moderately rugged

Frequency In Hertz:

400.0

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

280.0 ohms single winding and 300.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

3 unthreaded hole second mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Cubic Measure:

1.061 cubic inches

Mounting Facility Pattern:

Triangle second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.02 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

1.396 inches second mounting facility and 1.446 inches second mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

14 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300