

View Online at <https://aerobasegroup.com/nsn/5945-00-172-7707>

**Overall Length:**

1.025 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.615 inches second mounting facility and 0.635 inches second mounting facility

**Overall Height:**

1.010 inches

**Overall Width:**

1.025 inches

**Environmental Protection:**

Hermetic

**Unthreaded Mounting Hole Diameter:**

0.155 inches second mounting facility and 0.161 inches second mounting facility

**Fragility Factor:**

Moderately rugged

**Frequency In Hertz:**

400.0

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

280.0 ohms single winding and 300.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

3 unthreaded hole second mounting facility

**Storage Type:**

General purpose warehouse

**Features Provided:**

Polarized

**Cubic Measure:**

1.061 cubic inches

**Mounting Facility Pattern:**

Triangle second mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Time Delay:**

0.02 seconds fixed operate and release time

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

1.396 inches second mounting facility and 1.446 inches second mounting facility

**Operating Voltage Rating And Type At Specificationified Temp:**

28.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

2.0 amperes ac lamp load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

14 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03300