# NSN 5945-00-172-8224

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-172-8224	
Overall Length:	
1.320 inches	
Center To Center Distance Between Mounting Facilities Parallel To Length:	
1.078 inches single mounting facility	
Overall Height:	
0.410 inches	
Overall Width:	
0.612 inches	
Mounting Slot Width:	
0.150 inches single mounting facility	
Environmental Protection:	
Hermetic	
Fragility Factor:	
Moderately rugged	
Winding Quantity:	
1	
Purpose For Which Designed:	
General	
Coil Quantity:	
1	
Winding Dc Resistance Rating:	
600.0 ohms single winding and 900.0 ohms single winding	
Duty Type:	
Continuous	
Arc Quenching Method:	
Air	
Mounting Facility Type And Quantity:	
2 slotted hole single mounting facility	
Storage Type:	

General purpose warehouse

**Mounting Facility Pattern:** 

In-line single mounting facility

#### **Nonpile-up Main Contact Arrangement:**

2 pole, double throw, one position momentary

Time Delay:

0.004 seconds fixed operate time

### **Operating Voltage Rating And Type At Specificationified Temp:**

26.5 volts dc 25 degrees celsius single winding

### Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

# NSN 5945-00-172-8224

Electromagnetic Relay - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

8 pin all functions

### **Specification Data:**

81349-mil-r-5757/9 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300