## NSN 5945-00-173-4581

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-173-4581

The state of the s
Overall Length:
1.730 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches single mounting facility
Overall Height:
2.100 inches
Overall Width:
1.280 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Frequency In Hertz:
400.0
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Mounting Facility Pattern:
Triangle single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
60.00 seconds fixed operate time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.396 inches single mounting facility and 1.446 inches single mounting facility

115.0 volts ac 25 degrees celsius single winding

**Operating Voltage Rating And Type At Specificationified Temp:** 

## NSN 5945-00-173-4581

Electromagnetic Relay - Page 2 of 2



## Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes ac lamp load and 2.0 amperes dc lamp load

**Main Contact Maximum Voltage Rating In Volts:** 

115.0 ac and 28.0 dc

**Terminal Type And Quantity:** 

8 wire hook all functions

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A03300