# NSN 5945-00-189-0650

Electromagnetic Relay - Page 1 of 2



Viev	w Online at https://aerobasegroup.com/nsn/5945-00-189-0650
Ove	erall Length:
1.48	31 inches
Cen	nter To Center Distance Between Mounting Facilities Parallel To Length:
1.06	52 inches single mounting facility
Ove	erall Height:
0.41	10 inches
Ove	erall Width:
1.45	53 inches
Env	rironmental Protection:
Her	metic
Unt	hreaded Mounting Hole Diameter:
0.12	20 inches single mounting facility
Fra	gility Factor:
Mod	derately rugged
Win	ding Quantity:
1	
Pur	pose For Which Designed:
Ger	neral
Coi	l Quantity:
1	
Win	ding Dc Resistance Rating:
1.3	kilohms single winding and 1.7 kilohms single winding
Dut	y Type:
Con	ntinuous
Arc	Quenching Method:
Air	
Μοι	unting Facility Type And Quantity:
2 ur	nthreaded hole single mounting facility
Sto	rage Type:
Ger	neral purpose warehouse
Moi	unting Facility Pattern:

In-line single mounting facility

### Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

#### **Operating Current Rating And Type:**

11.0 milliamperes dc single winding

#### Time Delay:

0.015 seconds fixed operate time

### Main Contact Load Current Rating At Maximum Rated Voltage:

300.0 milliamperes ac resistive load and 2.0 milliamperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# NSN 5945-00-189-0650

Electromagnetic Relay - Page 2 of 2



#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Terminal Type And Quantity:**

8 pin all functions

#### **Specification Data:**

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300