

View Online at <https://aerobasegroup.com/nsn/5945-00-189-0753>

**Thread Class:**

2a single mounting facility

**Thread Direction:**

Right-hand single mounting facility

**Overall Length:**

1.390 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.354 inches single mounting facility

**Overall Height:**

1.406 inches

**Overall Width:**

0.734 inches

**Environmental Protection:**

Dustproof and shock resistant and vibration resistant

**Contact Material:**

Silver

**Contact Surface Treatment:**

Gold

**Winding Quantity:**

1

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

90.0 ohms single winding

**Duty Type:**

Continuous

**Mounting Facility Type And Quantity:**

1 threaded stud single mounting facility

**Thready Qty Per Inch (tpi):**

48 single mounting facility

**Thread Size:**

0.099 inches single mounting facility

**Nonpile-up Main Contact Arrangement:**

6 pole, double throw, one position momentary

**Time Delay:**

0.008 seconds fixed release time

**Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Energizing Element Power Rating:**

1.5 watts

**Precious Material And Location:**

Contact surfaces gold and contacts silver

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc single mounting facility

**Terminal Type And Quantity:**

20 tab, solder lug all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300