

View Online at <https://aerobasegroup.com/nsn/5945-00-189-0753>

Thread Class:

2a single mounting facility

Thread Direction:

Right-hand single mounting facility

Overall Length:

1.390 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.354 inches single mounting facility

Overall Height:

1.406 inches

Overall Width:

0.734 inches

Environmental Protection:

Dustproof and shock resistant and vibration resistant

Contact Material:

Silver

Contact Surface Treatment:

Gold

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

90.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

Thready Qty Per Inch (tpi):

48 single mounting facility

Thread Size:

0.099 inches single mounting facility

Nonpile-up Main Contact Arrangement:

6 pole, double throw, one position momentary

Time Delay:

0.008 seconds fixed release time

Operating Voltage Rating And Type At Specificationified Temp:

12.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Energizing Element Power Rating:

1.5 watts

Precious Material And Location:

Contact surfaces gold and contacts silver

Precious Material:

Gold and silver

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

20 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300