# NSN 5945-00-189-4397

Electromagnetic Relay - Page 1 of 2

1.406 inches single mounting facility

Overall Length: 1.750 inches

Overall Height: 1.612 inches Overall Width:



View Online at https://aerobasegroup.com/nsn/5945-00-189-4397

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

0.625 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
14.0 ohms single winding and 21.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
1.763 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
0.015 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
6.0 volts dc 25 degrees celsius single winding

## NSN 5945-00-189-4397

Electromagnetic Relay - Page 2 of 2



### Main Contact Load Current Rating At Maximum Rated Voltage:

800.0 milliamperes ac lamp load and 1.0 amperes dc lamp load

### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 wire hook all functions

#### **Specification Data:**

81349-mil-r-5757/23 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A03300