## NSN 5945-00-194-7589

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-194-7589

2.375 inches  Center To Center Distance Between Mounting Facilities Parallel To Length:  1.250 inches single mounting facility  Overall Height:  1.875 inches  Overall Width:  1.875 inches  Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
1.250 inches single mounting facility  Overall Height:  1.875 inches  Overall Width:  1.875 inches  Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Overall Height:  1.875 inches  Overall Width:  1.875 inches  Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
1.875 inches  Overall Width:  1.875 inches  Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Overall Width:  1.875 inches  Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility Winding Quantity:  1 Coil Quantity:  1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern:
Unthreaded Mounting Hole Diameter:  0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
0.190 inches single mounting facility  Winding Quantity:  1  Coil Quantity:  1  Duty Type:  Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Winding Quantity:  1 Coil Quantity:  1 Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern:
Coil Quantity:  Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern:
Coil Quantity:  1  Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Duty Type: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern:
Duty Type: Continuous  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Continuous  Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Mounting Facility Pattern:
2 unthreaded hole single mounting facility  Mounting Facility Pattern:
Mounting Facility Pattern:
In the calculation facility
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
1 pole, single throw, normally closed, momentary action
Operating Voltage Rating And Type At Specificationified Temp:
495.0 volts ac 25 degrees celsius single winding
Terminal Type And Quantity:
4 screw all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A03300