

View Online at <https://aerobasegroup.com/nsn/5945-00-200-9306>

**Overall Length:**

1.415 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.195 inches second mounting facility and 1.205 inches second mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.395 inches second mounting facility and 0.405 inches second mounting facility

**Overall Height:**

0.810 inches

**Overall Width:**

0.610 inches

**Environmental Protection:**

Hermetic and shock resistant

**Unthreaded Mounting Hole Diameter:**

0.091 inches second mounting facility and 0.101 inches second mounting facility

**Fragility Factor:**

Moderately rugged

**Winding Quantity:**

1

**Purpose For Which Designed:**

General

**Coil Quantity:**

1

**Winding Dc Resistance Rating:**

450.0 ohms single winding and 550.0 ohms single winding

**Duty Type:**

Continuous

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

4 unthreaded hole second mounting facility

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

0.699 cubic inches

**Mounting Facility Pattern:**

Rectangular second mounting facility

**Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

**Operating Current Rating And Type:**

27.0 milliamperes dc single winding

**Time Delay:**

0.006 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:**

13.5 volts dc 25 degrees celsius single winding

**Main Contact Load Current Rating At Maximum Rated Voltage:**

1.0 amperes dc inductive load

**Main Contact Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Terminal Type And Quantity:**

14 pin all functions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03300