NSN 5945-00-200-9337

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-200-9337

| Inread Class: |
|--|
| 2a single mounting facility |
| Thread Direction: |
| Right-hand single mounting facility |
| Overall Length: |
| 1.580 inches |
| Overall Height: |
| 1.397 inches |
| Overall Width: |
| 0.735 inches |
| Case Material: |
| Plastic |
| Environmental Protection: |
| Dustproof |
| Fragility Factor: |
| Moderately rugged |
| Contact Material: |
| Gold |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 350.0 ohms single winding |
| Duty Type: |
| Continuous |
| Arc Quenching Method: |
| Air |
| Mounting Facility Type And Quantity: |
| 1 threaded stud single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 1.622 cubic inches |
| Thready Qty Per Inch (tpi): |
| 48 single mounting facility |
| Thread Size: |
| 0.099 inches single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 8 pole, double throw, one position momentary |

NSN 5945-00-200-9337

Electromagnetic Relay - Page 2 of 2



Operating Voltage Rating And Type At Specificationified Temp: 5.0 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes ac resistive load and 250.0 milliamperes dc resistive load **Main Contact Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc **Precious Material And Location:** Contacts gold **Precious Material:** Gold **Thread Series Designator:** Unc single mounting facility **Terminal Type And Quantity:** 26 tab, solder lug all functions Shelf Life: N/a **Unit Of Measure:**

No

Fiig:

A03300

Demilitarization: