

View Online at <https://aerobasegroup.com/nsn/5945-00-201-5774>

**Thread Class:**

2a power takeoff facility stud

**Body Style:**

Cylindrical frame

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.031 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.750 inches

**Body Diameter:**

2.620 inches

**Mounting Slot Width:**

0.344 inches

**Body Length:**

5.359 inches

**Case Material:**

Steel

**Case Surface Treatment:**

Any acceptable

**Environmental Protection:**

Fungus proof

**Mounting Base Width:**

3.813 inches

**Actuator Length:**

1.610 inches

**Actuator Diameter:**

0.250 inches

**Frequency In Hertz:**

60.0

**Inclosure Type:**

Fully enclosed

**Magnetic Coil Quantity:**

1

**Electrical Resistance:**

Between 3.80 ohms and 4.20 ohms

**Duty Type:**

Intermittent

**Terminal Location:**

Base edge

**Voltage Rating In Volts:**

24.0 dc

**Mounting Facility Type And Quantity:**

4 slot

**Current Rating:**

6.000 amperes

**Thready Qty Per Inch (tpi):**

28 power takeoff facility stud

**Actuator Stroke Type:**

Pull and push

**Linear Force Delivered:**

14.00 pounds

**Power Takeoff Connection Type:**

External threads

**Energizing Stroke Maximum Length:**

0.500 inches

**Thread Size:**

0.250 inches power takeoff facility stud

**Mounting Facility Pattern:**

Four position rectangular

**Thread Series Designator:**

Unf power takeoff facility stud

**Terminal Type And Quantity:**

2 threaded stud

**Fsc Application Data:**

Electrical group, gasoline engine

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A134a0